

Power & Volume



Autonomous Airborne Surface Disinfection (ASD) device, with unique technique of dry fog using the centrifugation technique. In compliance with the **EN 17-272 norm**.

Marketing Authorisation **N° AMM FR-2019-0071** obtained with the **O2SAFE7.4® disinfectant**.

Technical characteristics

Volume treated: 50 up to 1665 m³

Device's flowrate: 4.2 L/hr

Diffusion time: 68 min for 400m³ at 12mL/m³ for example

Droplets size: 5 to 10 µm

Up to 5 consecutive cycles

Full stainless steel body

Liquid safety notification "Liquid inlet error" if the biocide tank is empty

Equipped with wheels and handles

Minimum maintenance, robust device

Biocide tank: 20 L (2x 10L)

Power: 120W

Size (l x w x h): 839 x 450 x 813 mm

Weight: 25 kg

Material compatible with O2SAFE7.4® & Phileasafe®

EN 17-272 compliant & Marketing Authorisation

Works on mains power

Power supply: 100-240V, 50/60Hz, 1.8A

Indication: final disinfection after cleaning

After-cleaning three-step disinfection



1- Diffusion

Microdrop Phase

Microdrop Technology®*: the biocide sprayed in non-wetting fog covers the entire surfaces

2- Contact time

Steam Phase

- Small droplet size allows to shorten the evaporation time
- Biocide enters the microbial cells and kills it

3- Aeration

Recovery after 20 air changes

Performance, Safety, Simplicity & Rapidity for the following applications:



Disinfection service provider



Food industry



Veterinary



Production or packaging areas

* Microdrops resulting from the centrifugation technique



Performance

- Effectiveness confirmed by the **Marketing Authorisation N°FR-2019-0071** and compliant with **EN 17-272**
- 4-log₁₀, 5-log₁₀, 6-log₁₀ microorganism decrease depending on the requirements
- Intensive use:** 2 x 10 L biocide tanks to treat very large volumes
- Very robust**, thanks to its stainless steel body

Rapidity

- Adaptation of the protocol according to the **goal** and **disinfection level** to achieve: up to sterilisation level
- Different zones & programs memorized (name, volume, biocide dose...) for fast disinfection cycle launch
- Microdrop Technology®:** dry fog nebulisation technology and optimised contact time
- Able to homogenously treat several rooms or large spaces at once thanks to its two diffusion heads

Security

- Remote monitoring with MyPhileas®:** no contact with the biocide
- Early notification if the biocide level is missing
- Maintenance kit** supply, for reliable disinfection cycle each time
- Management of accreditation level:** parameters of the zones can only be modified by the administrator (with a password)
- Compatible with O2SAFE7.4® and Phileasafe®: ≤7.4% H₂O₂ concentration, **safe for users and non corrosive for equipment**
- O2SAFE7.4® is 100% biodegradable, additive free and residue free

Control, data analysis & traceability

- Easy programming and total autonomy** with two criteria: volume & concentration
- Automatic calculation** of the diffusion time
- Variables and treatment area **memorisation functionality**
- Get a **high traceability level with MyPhileas®** application:
 - Available on **laptop (Android & Windows)** or **tablet** (can be provided) via Wifi connection
 - Remote control** during the disinfection cycle
 - Traceability of the previous diffusion reports** via MyPhileas® application
 - Information of the device's conditions



Why Devea?

- Biodecontamination expertise with the most demanding sectors & Marketing Authorisation
- Devea Services:**
 - Protocol support & personalized advice
 - Maintenance kit & step by step guided maintenance manual
 - Biological and chemical indicators provision
 - After-sale service & equipment repair diagnostic under 48hrs
- A range of products adapted for all volumes
- Design, manufacture and maintenance in France (Nantes)