



Optimised connectivity Excellent wifi connection Communication with the MyPhileas Optimum app

Screen 4.3 inches, color, easier browsing

Traceability, data integrity

Memory of all latest diffusions

Audited compliant 21CFR Part 11 & Annex 11 with MyPhileas Optimum 4 operator profiles, traceability of all operations Audit trail saved on the equipment Diffusion results visible on screen, exportable in pdf format

Technical characteristics

Treated volume 1 to 800m3* Device flowrate 3000 mL/h, biocide tank 10L Built-in weight sensor diffusion precision Droplet size 5 to 10µm Size (L x W x H) 815 x 250 x 840 mm, Weight 17 kg Multi-cycle Separate delay time and inter-cycle time Security "Insufficient liquid" if biocide quantity is low Supply power 150W Power supply mains 100-240V, 50/60Hz, 1.8A, Power supply equipment 24V DC, 6.25A max

Autonomous Airborne Surface Disinfection (ASD) device, with patented technology of non-wetting fog using the centrifugation technique. In compliance with EN 17-272 standards. Marketing Authorisation AMM N° FR-2019-0071 obtained with disinfectant **O2SAFE7.4®.**

PERFORMANCE, SAFETY & EASE OF USE FOR THE FOLLOWING **APPLICATIONS ACTIVITY SECTORS:**

- Pharmaceutical industry, research laboratory
- Large rooms, room (grade B) around a RABS, corridors

faccording to the calculation tank capacity / 12mL/m3 dose (Marketing Authorisation) ** Microdrop Technology: micro drops resulting from the centrifugation

DISINFECTION IN THREE STEPS

1 I Diffusion

Microdrop phase

Microdrop Technology®**: Biocide is sprayed in microdroplets, forming a nonwetting fog that covers all accessible and non-accessible excellent surfaces, with distribution.

2 I Contact time

Vapor phase

Evaporation of small droplets on contact with surfaces. Penetration of the biocide into microbial cell and irreversible lethal action (full biocide spectrum).

3 I Aeration

Low H₂O₂ concentration: fast ventilation.



PERFORMANCE

- Efficacy validated by Marketing Authorisation N°FR-2019-0071 and in compliance with EN 17-272 standards
- Microorganism reduction of 4, 5 and 6 log10 depending on requirements (Geobacillus stearothermophilus spores)
- Up to 10 successive cycles possible
- Easy to move and transport thanks to its multi-directional castors
- Preventive maintenance contract: guaranteed performance with every disinfection

EFFICIENCY

- Protocol can be adapted to meet specific disinfection targets
- Quick start-up thanks to program and zone memory (name, volume, biocide dose)
- MicrodropTechnology®: non-wetting fog technology and optimised contact time, short aeration time

SECURITY

- · Remote control with MyPhileas Optimum: no contact with biocide
- · Quick notification if biocide level is insufficient
- Easy, automatic programming, reducing the risk of errors
- Accreditation level management: zone parameters can only be modified by the supervisor profile
- Compatible with O2SAFE7.4® and Phileasafe®: concentration of $H_2O_2 \le 7.4\%$, safe for users and non-corrosive for equipment
- · Integrated immersion cap: no biocide handling



INTEGRATION E TRACEABILITY

- Point-to-point wifi communication, excellent connection with MyPhileas Optimum application (tablet or PC).
- Weight sensor under the biocide tank: diffusion data integration, sécurity message before diffusion starts if the biocide quantity is not enough to complete the diffusion

Traceability, data integrity:

- Diffusion report and audit trail exportable in pdf format
- Equipment audited compliant with GMP Annex 11 and 21CFR Part 11 with MyPhileas Optimum application

WHY CHOOSE DEVER?

- Biodecontamination expertise recognized in the most demanding sectors
- Range of products and services adapted to all configurations
- · Market Authorization issued

Devea Biodecontamtion Services offer:

- Qualifications (IQ, OQ)
- Cycle developpement, protocol, support & performance qualification
- Training
- · Disinfection service provision
- Annual preventive maintenance contract
- Biological and chemical indicators supply
- After-sales service & equipment diagnostics within 48 hours
- Designed, manufactured and maintained in France