

Phileas[®] Genius Optimum range

A concentrate of technology

EFFICIENT AND SAFE DISINFECTION IN THREE STEPS

1 I Diffusion Microdrop phase

Microdrop Technology®*: Biocide is sprayed in microdroplets, forming a nonwetting fog that covers all accessible and non-accessible surfaces, with excellent distribution.

2 I Contact time Vapor phase

Evaporation of small droplets on contact with surfaces. Penetration of the biocide into the microbial cell and irreversible lethal action (full biocide spectrum).

3 | Aeration

Low H_2O_2 concentration: fast ventilation.



Technical characteristics

New optimised interface Tactile interface (HMI) Operator identification at the start Screen 4.3 inches, color, easier browsing Memory of all latest diffusions

Optimised connectivity Excellent wifi connection Communication with the MyPhileas Optimum app

Traceability, data integrity

Audited compliant 21CFR Part 11 & Annex 11 with MyPhileas Optimum 4 operator profiles, traceability of all operations Audit trail saved on the equipment Diffusion results visible on screen, exportable in pdf format

Treated volume 0.5 to 5 m3 Device flowrate 400 mL/h, biocide tank 250mL Droplet size 5 to 10µm Size (L x W x H) 280 x 255 x 225 mm, Weight 7 kg Multi-cycle Separate delay time and inter-cycle time On battery (NiMh) charger supplied Power supply charger 100-240V, 50/60Hz, 1,8A, Power 45W

Autonomous Airborne Surface Disinfection (ASD) device, with patented technology of non-wetting fog using the centrifugation technique. In compliance with EN 17-272 standards. Marketing Authorisation AMM N° FR-2019-0071 obtained with disinfectant O2SAFE7.4®.

PERFORMANCE, SAFETY & EASE OF USE FOR THE FOLLOWING APPLICATIONS ACTIVITY SECTORS:

- Pharmaceutical industry, research laboratory
- Biosafety cabinets, isolators, incubators, passboxes

PERFORMANCE

- Efficacy validated by Marketing Authorisation N°FR-2019-0071 and in compliance with EN 17-272 standards
- Microorganism reduction of 4, 5 and **6 log10** depending on requirements (*Geobacillus stearothermophilus* spores)
- Up to 20 successive cycles possible
- Easy to move and place in the most confined spaces (isolators, incubators, etc.).
- Preventive maintenance contract: guaranteed performance with every disinfection

EFFICIENCY

- Protocol can be adapted to meet specific disinfection targets
- **Quick start-up** thanks to program and zone memory (name, volume, biocide dose)
- **MicrodropTechnology**®: non-wetting fog technology and optimised contact time, short aeration time

SECURITY

- · Remote control with MyPhileas Optimum: no contact with biocide
- Easy, automatic programming, reducing the risk of errors
- Accreditation level management: zone parameters can only be modified by the supervisor profile
- Compatible with O2SAFE7.4® and Phileasafe®: concentration of $H_2O_2 \le 7.4\%$, safe for users and non-corrosive for equipment
- Dosing pump for filling the reservoir (optional): no need to handle biocide



+33 2 40 57 07 40 puminski@devea-environnement.com 34 Bld Maréchal Alphonse Juin 44100 NANTES FRANCE

INTEGRATION ¢ TRACEABILITY

• Point-to-point wifi **communication**, excellent connection with MyPhileas Optimum application (tablet or PC).

Traceability, data integrity:

- Diffusion report and audit trail exportable in pdf format
- Equipment audited compliant with GMP Annex 11 and 21CFR Part 11 with MyPhileas Optimum application

WHY CHOSE DEVEA?

- Biodecontamination expertise recognized in the most demanding sectors
- Range of products and services adapted to all configurations
- Market Authorization issued

Devea Biodecontamtion Services offer:

- Qualifications (IQ, OQ)
- Cycle developpement, protocol, support & performance qualification
- Training
- Disinfection service provision
- Annual preventive maintenance contract
- Biological and chemical indicators supply
- After-sales service & equipment diagnostics within 48 hours
- Designed, manufactured and maintained in France

